

No.548-CKG SAG TESTER



JIS- (K5400)

FEATURE

This tester is used for measuring the flow (sag) or hiding power of paint.

SPECIFICATIONS

Coating thickness 75, 100, 150, 200, 250 μm
 Coating width 20mm \cdots 5lines
 Gap 3mm
 Dimensions \cdot W140xD30xH30mm \cdot 1kg
 Weight (Approx.)

※Special thickness and width model is available.

No.548-YKG FILM APPLICATOR (DOCTOR BLADE)



JIS-K5101, (K5400)

FEATURE

This instrument is used for forming specified thickness coating of ink or paint.

SPECIFICATIONS

Coating thickness 2~10mil (1mil=25.4 μm)
 Coating width 80mm
 Dimensions \cdot W100xD30xH30mm \cdot 0.7kg
 Weight (Approx.)

※Special thickness and width model is available.

※Special 2sides, 3sides, 4sides model is available.

No.549 NO PICK UP TIME TESTER FOR TRAFFIC PAINT



JIS-K5665, ASTM-D711

FEATURE

This tester is used for measuring the drytime of traffic paint.

SPECIFICATIONS

Tyre Diameter ϕ 241 \pm 6mm, Top R8 \pm 1mm
 Over-all width 368mm
 Weight 15.8 \pm 0.2kg