

Elcometer 204 Steel Ultrasonic Thickness Gauge



Elcometer 204 Steel Ultrasonic Thickness Gauge

At a glance:

Low cost method of testing material thickness

Measure material thickness when there is only access to one side eg: pipes, tanks etc.

Hand held, fast and accurate

The Elcometer 204 Steel Ultrasonic Thickness gauge is a handheld gauge providing fast and accurate measurements of the thickness of steel. The principal advantage of ultrasonic measurement over traditional methods is that ultrasonic measurements can be performed with access to only one side of the material being measured.

The Elcometer 204 is pre-calibrated for ease of use and the gauge can be “zeroed” to ensure accuracy.

Battery powered, the Elcometer 204 features an easy read backlit screen making it ideal for use in low light areas. Supplied with everything required to start measuring as soon as the gauge is received, the Elcometer 204 provides an ideal, low cost solution for measuring thickness of steel.

- **Low cost and easy to use:**
Provided with everything required to use straight from the box.
- **Probe Zero:**
“Zeroing” the gauge ensures correct measurements.

Material Thickness

The thickness of materials cannot always be determined by direct measurement as access to both sides is not always possible.

The effects of corrosion and erosion at the back of a metal panel may reduce its thickness significantly yet not affect the front surface. Pipelines, for example, may appear corrosion free on the outside but can be eroded by the flow of material on the inside.

Machined or cast items may have thin walls that cannot be determined by callipers or other non-destructive tests.

Range	0.63mm to 199.99mm (0.025" to 19.999")
Resolution	0.01mm (0.001")
Accuracy	±2% of reading or ±0.5mm (±0.02"), depending on material and conditions
Weight	295g (10oz) including batteries
Size	63.5 x 120.6 x 31.5mm (2.5 x 4.5 x 1.24")
Operating temperature	-30°C to 50°C (-20°F to 120°F) depending on climatic conditions
Case	Extruded aluminium body, Nickel plated aluminium end caps
Battery life*	200 hours continuous (alkaline dry batteries)
Battery type	2 x LR6 (AA), alkaline dry batteries or rechargeable equivalents.
Packing list	Elcometer 204 Steel Ultrasonic Thickness Gauge, Transducer with calibration certificate, bottle of couplant, 2 x batteries, carrying case, operating instructions
Part Number	C204----1

* Rechargeable batteries can be used if they are recharged outside the gauge.
 Battery life is reduced to approximately 120 hours when using rechargeable batteries.

Spares / Accessories	
Transducer: Potted right angle 5.0MHz ¼"	T92015646
Ultrasonic Couplant	T92015701
High Temperature Ultrasonic Couplant	T92015874
Instrument Carry Case	T92015617
Test Wedge: 2-25mm	T9205243-
Test Wedge: 30-100mm	T9205270-

Related Products:



Elcometer 205, 206 & 206DL
Ultrasonic Thickness Gauges

Elcometer have a range of products to establish material thickness.

Elcometer 205, 206 & 206DL Ultrasonic Thickness Gauges have three calibration options can be used for measuring many different materials including steel, cast iron, plastic, epoxy resin, glass fibre etc.



Elcometer 208 & 208DL
Ultrasonic Thickness Gauges

Elcometer 208 & 208DL Ultrasonic Thickness Gauges are capable of measuring material thickness whilst eliminating the thickness of the coating (on metal substrates only).
 The Elcometer 208DL has data logging capability and data can be transferred onto PC.



Elcometer 207 & 207DL
Ultrasonic Thickness Gauges

Elcometer 207 & 207DL Precision Ultrasonic Gauges are designed to provide accurate measurements on thin materials including cast iron, plastic, steel, glass, aluminium and thin plastics.
 The Elcometer 207DL is able to store 1000 readings in 10 batches.

ENGLAND

Elcometer Limited
 Edge Lane
 Manchester M43 6BU
 Tel: +44 (0)161 371 6000
 Fax: +44 (0)161 371 6010
 e-mail: sales@elcometer.com
 www.elcometer.com

USA

Elcometer Inc
 1893 Rochester Industrial Drive
 Rochester Hills Michigan 48309
 Tel: +1 248 650 0500
 Toll Free: 800 521 0635
 Fax: +1 248 650 0501
 e-mail: inc@elcometer.com
 www.elcometer.com

ASIA & THE FAR EAST

Elcometer (Asia) Pte Ltd
 896 Dunearn Rd
 Sime Darby Centre #3-09
 Singapore 589472,
 Republic of Singapore

Tel: +65 6462 2822
 Fax: +65 6462 2860
 e-mail: asia@elcometer.com
 www.elcometer.com

BELGIUM

Elcometer SA
 Rue Vallée 13
 B-4681 Hermalle /s Argenteau

Tel: +32 (0)4 379 96 10
 Fax: +32 (0)4 374 06 03
 e-mail: be_info@elcometer.be
 www.elcometer.be

FRANCE

Elcometer Sarl
 97 Route de Chécy
 45430 BOU

Tel: +33 (0)2 38 86 33 44
 Fax: +33 (0)2 38 91 37 66
 e-mail: fr_info@elcometer.fr
 www.elcometer.fr

GERMANY

Elcometer Instruments GmbH
 Ulmer Strasse 68
 D-73431 Aalen

Tel: +49 (0)7361 52806 0
 Fax: +49 (0)7361 52806 77
 e-mail: de_info@elcometer.de
 www.elcometer.de