

Complies with the requirements of

ASTM G62-87(1998), NACE RP0274-98, NACE RP0490-2001, NACE RPO188-99, ASTM D4787-93(1999), JIS G-3491, JIS G-3492, ANSI/AWWA C214-89, ANSI/AWWA C213-94 and ISO 2746:1998

Application

- Porosity detection of Tanks, Valves, Pumps, Pipeline field joints, and general inspection and maintenance.
- Suitable for a broad range of testing and inspection requirements. It is recommended that the integral probe be limited to a 125mm flat brush or fan brush.

Features

- LED bargraph display of voltage
- "Single" hand-held, lightweight unit for simplicity and ease of operation
- Audible and visual alarms
- LED battery condition indicator
- Integral probe

Voltages

Two Models:

- Variable output up to 10kV
- Variable output up to 20kV

Specifications

Test Voltage: to 10kV (using 9V Battery)
to 20kV (using 12V external Batt)

Output test current: up to 100µA

Operating temperature: -20 to +50°C

Power supply: Battery (9V internal)
Battery (12V external for extended use)

Unit Dimensions: 210 x 75 x 35mm (excl brush)
8.25" x 3.1" x 1.5"

Unit Weight: 460g (incl probe)

Shipping Weight: 1.5kg
2.1kg (with extended-use power-pack)



NEW

Kit comprises

- Detector
- 7m Earth lead and clamp
- Flat 125mm wide brass wire brush (or optional fan brush)
- Carry Case
- Operating instructions with conformance certificate

Order from



Made in AUSTRALIA

PCWI International Pty Ltd
13 Alhambra Avenue CARDIFF NSW 2285
Ph: (02) 4954 3900 • Fax: (02) 4954 3999
email: sales@pcwi.com.au • http://www.pcwi.com.au



NDT Supply.com, Inc.
P.O. Box 7350
Shawnee Mission, KS 66207-0350

913-685-0675, fax 913-685-1125
e-mail: sales@ndtsupply.com
www.ndtsupply.com