

Orbit \square LS Low Speed Shaker



- Economical analog control with easy-turn knobs
- 19 mm orbit for blotting, gel staining and general mixing
- Streamlined design
- Safe for cold room and incubator use

CSA compliant

Product Information

The Orbit LS low speed shaker is a high quality, general purpose shaker with economical analog control.

Styled after the other models in the line, the Orbit LS features a streamlined, compact design with easy-access control panel. Electronic controls are utilized for setting speed and time. The knobs used for selecting parameters turn easily and are clearly marked with corresponding values.

A large orbit and low speed make the Orbit LS useful for staining and destaining gels, washing blots and general mixing. The shaker is supplied with a 30 x 30 cm stainless steel flat platform and non-slip rubber mat to keep plates, dishes and other sample containers in place.

Safe for use in temperature controlled environments, the small profile of this shaker makes it ideal for use in incubators such as the Labnet 311 and 611 series.

Product Specifications

Speed range	3 - 60 rpm
Timer	20 - 120 min (10 min inc.) or continuous
Motion	Circular, 19 mm
Maximum load	11 lb/5 kg
Ambient operating range	+4° to 70°C
Dimensions (W x D x H)	10 x 12.6 x 6.3 in/25.5 x 32 x 16 cm
Weight	14.5 lb/6.6 kg
Electrical	120V~, 60 Hz or 230V~, 50 Hz

Ordering Information

Catalog Number	Item Description	Price
S2030-LS	Orbit LS Low Speed Orbital Shaker with flat platform	Request Quote
S2025-ST	Gel staining tray, pack of 4	Request Quote
S2031-12D	Stacked double flat platform with rubber mat	Request Quote

To order product in 230V, add -230V to the end of the catalog number